

Safety Data Sheet According to SANS 10234:2008 and SANS 11014:2010 Issue date:27/03/2020 Revision date: 28/03/2022

Version: 1.0

:

SECTION 1: Identification 1.1. Product identifier Product form Trade name Type of product Product code Product group 1.2. Relevant identified uses of No additional information available 1.3. Supplier's details Manufacturer Shield Chemicals (Pty) Ltd 9 London Rd Apex P.O. Box 1939 1501 Benoni - South Africa	: Kids bath : 20801400 : Trade pro)2, 214987001, 222885001 duct		58
Product form Trade name Type of product Product code Product group 1.2. Relevant identified uses of No additional information available 1.3. Supplier's details Manufacturer Shield Chemicals (Pty) Ltd 9 London Rd Apex P.O. Box 1939 1501 Benoni - South Africa	: Fozzi's foa : Kids bath : 20801400 : Trade pro	product)2, 214987001, 222885001 duct		58
Trade name Type of product Product code Product group 1.2. Relevant identified uses of No additional information available 1.3. Supplier's details Manufacturer Shield Chemicals (Pty) Ltd 9 London Rd Apex P.O. Box 1939 1501 Benoni - South Africa	: Fozzi's foa : Kids bath : 20801400 : Trade pro	product)2, 214987001, 222885001 duct		58
Type of product Product code Product group 1.2. Relevant identified uses of No additional information available 1.3. Supplier's details Manufacturer Shield Chemicals (Pty) Ltd 9 London Rd Apex P.O. Box 1939 1501 Benoni - South Africa	: Kids bath : 20801400 : Trade pro	product)2, 214987001, 222885001 duct		58
Product code Product group 1.2. Relevant identified uses of No additional information available 1.3. Supplier's details Manufacturer Shield Chemicals (Pty) Ltd 9 London Rd Apex P.O. Box 1939 1501 Benoni - South Africa	: Kids bath : 20801400 : Trade pro	product)2, 214987001, 222885001 duct		58
Product code Product group 1.2. Relevant identified uses of No additional information available 1.3. Supplier's details Manufacturer Shield Chemicals (Pty) Ltd 9 London Rd Apex P.O. Box 1939 1501 Benoni - South Africa	: 20801400 : Trade pro)2, 214987001, 222885001 duct		58
Product group 1.2. Relevant identified uses of No additional information available 1.3. Supplier's details Manufacturer Shield Chemicals (Pty) Ltd 9 London Rd Apex P.O. Box 1939 1501 Benoni - South Africa	: Trade pro	duct		
Acceleration Relevant identified uses of No additional information available 1.3. Supplier's details Manufacturer Shield Chemicals (Pty) Ltd Shield Chemicals (Pty) Ltd London Rd Apex P.O. Box 1939 501 Benoni - South Africa	•		ainst	
Ao additional information available .3. Supplier's details Manufacturer Shield Chemicals (Pty) Ltd D London Rd Apex P.O. Box 1939 501 Benoni - South Africa		iure and uses advised ag	amst	
.3. Supplier's details Manufacturer Shield Chemicals (Pty) Ltd London Rd Apex P.O. Box 1939 501 Benoni - South Africa				
Manufacturer Shield Chemicals (Pty) Ltd J London Rd ypex P.O. Box 1939 501 Benoni - South Africa				
T (011) 421 7111 info@shieldchem.co.za 1.4. Emergency telephone num Emergency number SECTION 2: Hazards identifie 2.1. Classification of the subst Classification according to the United Aerosol, Category 3 Serious eye damage/eye irritation Not	: (011) 421 cation ance or mixture ed Nations GHS classified	H229		
lazardous to the aquatic environment	- Acute Hazard Not cla	ssified		
Full text of H statements : see section	16			
2.2. Label elements				
Labelling according to the United Na Signal word (GHS-ZA) Hazardous ingredients Hazard statements (GHS-ZA) Precautionary statements (GHS-ZA)	: Warning : propane; l : H229 - Pr : P210 - Ke smoking. P251 - Do	butane, liquefied, under pre essurised container: May b ep away from heat, hot sur o not pierce or burn, even a 12 - Protect from sunlight. E	ourst if heated. rfaces, sparks, open flar fter use.	mes and other ignition sources. No ratures exceeding 50 °C.
2.3. Other hazards		g		
Adverse physicochemical, human heal environmental effects		ed container: May burst if h	eated.	
SECTION 3: Composition/inf	ormation on ingre	dients		
.1. Substances				
lot applicable				
3.2. Mixtures			-	
Name	Pr	oduct identifier	%	Classification according to the United Nations GHS
butane, liquefied, under pressure	(CA	AS-No.) 106-97-8	5.0 - 10.0	Pyr. Gas Not classified Flam. Gas 1, H220 Aquatic Acute 2, H401
propane	(CA	AS-No.) 74-98-6	1.0 - 5.0	Pyr. Gas Not classified Flam. Gas 1, H220 Aquatic Acute Not classified
	16			
Full text of H-statements: see section f				
	es			
Full text of H-statements: see section 1 SECTION 4: First aid measur 4.1. Description of first aid mea				
SECTION 4: First aid measur	asures	person to fresh air and keep	comfortable for breath	ing.

Fozzi's foam for fun - Groovy green Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

ccording to SANS 10234:2008 and SANS 11014:201	10
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
4.2. Most important symptoms and eff	fects, both acute and delayed
No additional information available	
4.3. Indication of any immediate media	cal attention and special treatment needed
Treat symptomatically.	
SECTION 5: Firefighting measures	3
5.1. Extinguishing media	
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
5.2. Special hazards arising from the	substance or mixture
Explosion hazard	: Pressurised container: May burst if heated.
•	
5.3. Advice for firefighters Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing
rotection during menghung	apparatus. Complete protective clothing.
SECTION 6: Accidental release me	22511705
	equipment and emergency procedures
No additional information available	equipment and emergency procedures
6.1.1. For non-emergency personnel	
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking.
6.1.2. For emergency responders Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information
	refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Avoid release to the environment.	
	ment and electrics up
6.3. Methods and material for contain	ment and cleaning up
6.3. Methods and material for contain Methods for cleaning up	: Mechanically recover the product.
Methods for cleaning up Other information	Mechanically recover the product.Dispose of materials or solid residues at an authorized site.
Methods for cleaning up	Mechanically recover the product.Dispose of materials or solid residues at an authorized site.
Methods for cleaning up Other information SECTION 7: Handling and storage	Mechanically recover the product.Dispose of materials or solid residues at an authorized site.
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling Precautions for safe handling	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling Precautions for safe handling Hygiene measures	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, inclu	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Inding any incompatibilities Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well ventilated place. Keep cool.
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, inclu Storage conditions	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Inding any incompatibilities Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well ventilated place. Keep cool.
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, inclu Storage conditions SECTION 8: Exposure controls/pe	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Inding any incompatibilities Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well ventilated place. Keep cool.
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, inclu Storage conditions SECTION 8: Exposure controls/per 8.1. Control parameters	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Iding any incompatibilities Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well ventilated place. Keep cool.
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, inclu Storage conditions SECTION 8: Exposure controls/pe 8.1. Control parameters propane (74-98-6)	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Iding any incompatibilities Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well ventilated place. Keep cool.
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, inclu Storage conditions SECTION 8: Exposure controls/pel 8.1. Control parameters propane (74-98-6) South Africa - Occupational Exposure Lin	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Iding any incompatibilities Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, inclu Storage conditions SECTION 8: Exposure controls/pe 8.1. Control parameters propane (74-98-6) South Africa - Occupational Exposure Lin Local name	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Iding any incompatibilities Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well ventilated place. Keep cool.
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, inclu Storage conditions SECTION 8: Exposure controls/pe 8.1. Control parameters propane (74-98-6) South Africa - Occupational Exposure Lin Local name OEL TWA (mg/m ³)	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. reding any incompatibilities Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well ventilated place. Keep cool.
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, inclu Storage conditions SECTION 8: Exposure controls/pe 8.1. Control parameters propane (74-98-6) South Africa - Occupational Exposure Lin Local name OEL TWA (mg/m ³) OEL TWA (ppm)	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Iding any incompatibilities Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well ventilated place. Keep cool.
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, inclu Storage conditions SECTION 8: Exposure controls/pe 8.1. Control parameters propane (74-98-6) South Africa - Occupational Exposure Lin Local name OEL TWA (mg/m ³) OEL TWA (ppm) Regulatory reference	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Iding any incompatibilities Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well ventilated place. Keep cool. Instant (Airborne Pollutants) Propane 1800 mg/m³ 1000 ppm Government Notice No. R 904
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, inclu Storage conditions SECTION 8: Exposure controls/pel 8.1. Control parameters propane (74-98-6) South Africa - Occupational Exposure Lin Local name OEL TWA (mg/m ³) OEL TWA (ppm) Regulatory reference butane, liquefied, under pressure (106-97-	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Iding any incompatibilities Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well ventilated place. Keep cool. Instant (Airborne Pollutants) Propane 1800 mg/m³ 1000 ppm Government Notice No. R 904
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, inclu Storage conditions SECTION 8: Exposure controls/pe 8.1. Control parameters propane (74-98-6) South Africa - Occupational Exposure Lin Local name OEL TWA (mg/m³) OEL TWA (ppm) Regulatory reference butane, liquefied, under pressure (106-97- South Africa - Occupational Exposure Lin Local name OEL TWA (mg/m³)	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Iding any incompatibilities Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well ventilated place. Keep cool. Inits (Airborne Pollutants) Propane 1800 mg/m³ 1000 ppm Government Notice No. R 904 -8)
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, inclu Storage conditions SECTION 8: Exposure controls/pe 8.1. Control parameters propane (74-98-6) South Africa - Occupational Exposure Lin Local name OEL TWA (mg/m³) OEL TWA (ppm) Regulatory reference butane, liquefied, under pressure (106-97- South Africa - Occupational Exposure Lin Local name OEL TWA (ppm) Regulatory reference	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Iding any incompatibilities Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well ventilated place. Keep cool. Instending Information Pollutants) Propane 1800 mg/m³ 1000 ppm Government Notice No. R 904 -8) mits (Recommended Limits) Butane 1430 mg/m³ 600 ppm
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, inclu Storage conditions SECTION 8: Exposure controls/pe 8.1. Control parameters propane (74-98-6) South Africa - Occupational Exposure Lin Local name OEL TWA (mg/m³) OEL TWA (ppm) Regulatory reference butane, liquefied, under pressure (106-97- South Africa - Occupational Exposure Lin Local name OEL TWA (ppm) Regulatory reference butane, liquefied, under pressure (106-97- South Africa - Occupational Exposure Lin Local name OEL TWA (ppm) OEL TWA (ppm) OEL TWA (ppm) OEL TWA (ppm)	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Iding any incompatibilities Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well ventilated place. Keep cool. Instended protection Propane 1800 mg/m³ 1000 ppm Government Notice No. R 904 For the sum of the store of
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, inclu Storage conditions SECTION 8: Exposure controls/pe 8.1. Control parameters propane (74-98-6) South Africa - Occupational Exposure Lin Local name OEL TWA (mg/m ³) OEL TWA (ppm) Regulatory reference butane, liquefied, under pressure (106-97- South Africa - Occupational Exposure Lin Local name OEL TWA (mg/m ³) OEL TWA (mg/m ³) OEL TWA (ppm) OEL STEL (mg/m ³) OEL STEL (mg/m ³)	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Iding any incompatibilities Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well ventilated place. Keep cool. rsonal protection Propane 1800 mg/m³ 1000 ppm Government Notice No. R 904 8) mits (Recommended Limits) Butane 1430 mg/m³ 600 ppm 1780 mg/m³ 750 ppm
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, inclu Storage conditions SECTION 8: Exposure controls/per 8.1. Control parameters propane (74-98-6) South Africa - Occupational Exposure Lin Local name OEL TWA (mg/m ³) OEL TWA (ppm) Regulatory reference butane, liquefied, under pressure (106-97- South Africa - Occupational Exposure Lin Local name OEL TWA (ppm) Regulatory reference butane, liquefied, under pressure (106-97- South Africa - Occupational Exposure Lin Local name OEL TWA (mg/m ³) OEL TWA (ppm) Regulatory reference	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Iding any incompatibilities Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well ventilated place. Keep cool. Instemperation Pollutants) Propane 1800 mg/m³ 1000 ppm Government Notice No. R 904 Butane 1430 mg/m³ 600 ppm 1780 mg/m³ 750 ppm Government Notice. R: 1179
Methods for cleaning up Other information SECTION 7: Handling and storage 7.1. Precautions for safe handling Precautions for safe handling Hygiene measures 7.2. Conditions for safe storage, inclu Storage conditions SECTION 8: Exposure controls/pe 8.1. Control parameters propane (74-98-6) South Africa - Occupational Exposure Lin Local name OEL TWA (mg/m ³) OEL TWA (ppm) Regulatory reference butane, liquefied, under pressure (106-97- South Africa - Occupational Exposure Lin Local name OEL TWA (mg/m ³) OEL TWA (mg/m ³) OEL TWA (ppm) OEL STEL (mg/m ³) OEL STEL (mg/m ³)	 Mechanically recover the product. Dispose of materials or solid residues at an authorized site. Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Iding any incompatibilities Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well ventilated place. Keep cool. Instemperation Pollutants) Propane 1800 mg/m³ 1000 ppm Government Notice No. R 904 Butane 1430 mg/m³ 600 ppm 1780 mg/m³ 750 ppm Government Notice. R: 1179

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

OEL TWA (mg/m³)	1430 mg/m ³	
OEL TWA (ppm)	600 ppm	
OEL STEL (mg/m ³)	1780 mg/m ³	
OEL STEL (ppm)	750 ppm	
Regulatory reference	Government Notice No. R 904	

o.z. Appropriate engineering controls	
Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.
8.3. Individual protection measures, suc	h as personal protective equipment (PPE)
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment

8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and o	chemical properties
Physical state	: Liquid
Appearance	: Liquid.
Colour	: Green.
Odour	: Apple.
Odour threshold	: No data available
pH	: 4.8 - 5.8
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Vapour pressure at 50 °C	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Relative density of saturated gas/air mixture	: No data available
Density	: No data available
Relative gas density	: No data available
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosive limit (LEL)	: No data available
Upper explosive limit (UEL)	: No data available
9.2. Other information	

No additional information available

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

SECT	ION 10: Stability and reactivity				
10.1.	Reactivity				
Pressur	Pressurised container: May burst if heated.				
10.2.	Chemical stability				
Stable u	Stable under normal conditions.				
10.3.	Possibility of hazardous reactions				
No dan	gerous reactions known under normal conditions of use.				
10.4.	Conditions to avoid				
Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.					
10.5.	Incompatible materials				
No additional information available					
10.6.	Hazardous decomposition products				
Under normal conditions of storage and use, hazardous decomposition products should not be produced.					

SECTION 11: Toxicological information

11.1.	Information on toxicological effect	ts	
A			Net de strat
Acute toxicity (oral)			Not classified
Acute to	oxicity (dermal)	:	Not classified
Acute to	exicity (inhalation)	:	Not classified

propane (74-98-6)		
LC50 inhalation rat (ppm)	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))	
butane, liquefied, under pressure (10	6-97-8)	
LC50 inhalation rat (mg/l)	1442.738 - 1443 mg/l 15 MIN	
LC50 inhalation rat (ppm)	800000 ppm 15 MIN	
Skin corrosion/irritation	: Not classified	
	pH: 4.8 - 5.8	
Serious eye damage/irritation	: Not classified.	
	pH: 4.8 - 5.8	
Pospiratory or skip consitisation	• Not elassified	

Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

Fozzi's foam for fun - Groovy green Vaporizer

Vaporizer	Aerosol
SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
propane (74-98-6)	
LC50 fish 1	24 mg/l (96 h, Pisces, Literature study)
LC50 fish 2	49.9 mg/l (96 h, Pisces, Fresh water, QSAR)
EC50 Daphnia 1	7 mg/l (48 h, Daphnia magna, Literature study)
BCF fish 1	9 - 25 (Pisces, QSAR)
Log Pow	1.09 - 2.8 (Experimental value, 20 °C)
butane, liquefied, under pressure (106-97-8)	
LC50 fish 1	> 1000 mg/l (96 h, Pimephales promelas, QSAR)
EC50 72h algae (1)	5.3 - 5.5 mg/l (Algae, QSAR)
01/03/2021	EN (English) 4

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

butane, liquefied, under pressure (106-97-8)		
Log Pow	2.89 (Experimental value)	
12.2. Persistence and degradability		
Fozzi's foam for fun - Groovy green		
Persistence and degradability	No additional information available	
propane (74-98-6)		
Persistence and degradability	Readily biodegradable in water.	
butane, liquefied, under pressure (106-97-8)		
Persistence and degradability	Readily biodegradable in water.	
12.3. Bioaccumulative potential		
Fozzi's foam for fun - Groovy green		
Bioaccumulative potential	No additional information available	
propane (74-98-6)		
BCF fish 1	See section 12.1 on ecotoxicology	
Log Pow	See section 12.1 on ecotoxicology	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
butane, liquefied, under pressure (106-97-8)		
Log Pow	See section 12.1 on ecotoxicology	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
12.4. Mobility in soil		
Fozzi's foam for fun - Groovy green		
Mobility in soil	No additional information available	
propane (74-98-6)		
Surface tension	0.016 N/m (-47 °C)	
Log Pow	See section 12.1 on ecotoxicology	
Ecology - soil	Not applicable (gas).	
butane, liquefied, under pressure (106-97-8)		
Surface tension	< 0.1 N/m (0 °C)	
Log Pow	See section 12.1 on ecotoxicology	
Ecology - soil	Not applicable (gas).	
12.5. Other adverse effects		
Ozone	: Not classified	
Other adverse effects	: No additional information available	

SECTION 13: Disposal considerations 13.1. Disposal methods

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information In accordance with SANS / IMDG / IATA

SANS	IMDG	ΙΑΤΑ	
14.1. UN number			
1950	1950	1950	
14.2. Proper Shipping Name			
AEROSOLS	AEROSOLS	Aerosols, non-flammable	
14.3. Transport hazard class(es)			
2.2	2.2	2.2	
		Not applicable	
14.4. Packing group			
Not applicable	Not applicable	Not applicable	
14.5. Environmental hazards			
Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No	

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

No supplementary information available 8, 190 9e SP277 9e SP277 003	
8, 190 ee SP277 ee SP277	
ee SP277 ee SP277	
ee SP277 ee SP277	
ee SP277 ee SP277	
ee SP277	
003	
P17, PP87	
3, 190, 277, 327, 344, 381, 959	
207, LP200	
P87, L2	
D - FIRE SCHEDULE Delta - FLAMMABLE G	GASES
U - SPILLAGE SCHEDULE Uniform - GASES	S (FLAMMABLE, TOXIC OR CORROSIVE)
one	
)	
203	
)kgG	
)3	
5kg	
)3	
50kg	
98, A145, A167, A802	
-	
	03 kgG 3 kg 3 0kg 8, A145, A167, A802

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

SECTION 16: Other information	
Issue date	: 27/03/2020
Revision date	: 28/03/2022

Full text of H-statements:

H220	Extremely flammable gas.
H226	Flammable liquid and vapour.
H227	Combustible liquid
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H303	May be harmful if swallowed
H311	Toxic in contact with skin.
H313	May be harmful in contact with skin
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H318 H319 H373 H400 H401 H402 H410	Causes serious eye damage. Causes serious eye irritation. May cause damage to organs through prolonged or repeated expos Very toxic to aquatic life. Toxic to aquatic life Harmful to aquatic life Very toxic to aquatic life with long lasting effects.

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.