

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010 Issue date: 2/28/2024 Revision date: 2/28/2026 Version: 1.0

SECTION 1: Identification

1.1. Product identifier		
Product form Trade name Type of product Product code Product group	 Mixture Fozzi's kids sunscreen lotion spray SPF50 Sunscreen products SH1506 Trade product 	
1.2. Relevant identified uses of the substa	ance or mixture and uses advised against	
Use of the substance/mixture	: Sunscreen products	
1.3. Supplier's details		
Manufacturer Shield Chemicals (Pty) Ltd 9 London Rd Apex P.O. Box 1939 1501 Benoni – Gauteng South Africa T (011) 421 7111 Contact: Jayson Clark		
1.4. Emergency telephone number		
Emergency number	: (011) 421 7111	
SECTION 2: Hazards identification 2.1. Classification of the substance or mixture Classification according to the United Nations GHS Aerosol, Category 1 H222;H229 Full text of H-statements: see section 16		
2.2. Label elements		
Labelling according to the United Nations GHS Hazard pictograms (GHS ZA)		
Signal word (GHS-ZA) Hazard statements (GHS ZA) Precautionary statements (GHS ZA)	 Danger H222 - Extremely flammable aerosol H229 - Pressurised container: May burst if heated P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. 	
2.3. Other hazards		
Adverse physicochemical, human health and environmental effects	: Pressurised container: May burst if heated, Extremely flammable aerosol.	

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
butane, liquefied, under pressure	CAS-No.: 106-97-8 EC Index-No.: 601-004-00-0	10.0 - 20.0	Flam. Gas 1, H220 Pyr. Gas Not classified Press. Gas (Liq.), H280 Acute Tox. Not classified (Inhalation:gas)
octocrilene	CAS-No.: 6197-30-4	5.0 - 10.0	Flam. Liq. Not classified Acute Tox. Not classified (Oral) Acute Tox. 5 (Dermal), H313 STOT RE Not classified Aquatic Acute 1, H400
Butylmethoxy dibenzoylmethane	CAS-No.: 70356-09-1	1.0 - 5.0	Acute Tox. Not classified (Oral) STOT RE Not classified Aquatic Acute 1, H400
(3,3,5-trimethylcyclohexyl) 2-hydroxybenzoate	CAS-No.: 118-56-9	1.0 - 5.0	Flam. Liq. Not classified Acute Tox. Not classified (Oral) Acute Tox. Not classified (Dermal) Aquatic Acute 3, H402
Ethylhexyl salicylate	CAS-No.: 118-60-5	1.0 - 5.0	Flam. Liq. Not classified Acute Tox. Not classified (Oral) Acute Tox. Not classified (Dermal) STOT RE Not classified Aquatic Acute 2, H401
propane	CAS-No.: 74-98-6 EC Index-No.: 601-003-00-5	1.0 - 10.0	Flam. Gas 1, H220 Pyr. Gas Not classified Press. Gas (Liq.), H280 Acute Tox. Not classified (Inhalation:gas) Aquatic Acute Not classified

SECTION 4: First aid measures		
4.1. Description of first aid measures		
First-aid measures after inhalation First-aid measures after skin contact First-aid measures after eye contact First-aid measures after ingestion	 Remove person to fresh air and keep comfortable for breathing. Wash skin with plenty of water. Rinse eyes with water as a precaution. Call a poison center or a doctor if you feel unwell. 	
4.2. Most important symptoms and effects, both acute and delayed		
No additional information available		
4.3. Indication of any immediate medical attention and special treatment needed		
Treat symptomatically.		
SECTION 5: Firefighting measures		

5.1. Extinguishing media

Suitable extinguishing media

: Water spray. Dry powder. Foam. Carbon dioxide.

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

5.2. Special hazards arising from the substance or mixture		
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 Extremely flammable aerosol. Pressurised container: May burst if heated. Toxic fumes may be released. 	
5.3. Advice for firefighters		
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.	

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equipment and emergency procedures		
No additional information available		
6.1.1. For non-emergency personnel		
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking.	
6.1.2. For emergency responders		
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
6.2. Environmental precautions		
Avoid release to the environment.		
6.3. Methods and material for containment and cleaning up		

Methods for cleaning up	:	Mechanically recover the product.
Other information	:	Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and store	age	
7.1. Precautions for safe handling		
Precautions for safe handling Hygiene measures	 Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. 	
7.2. Conditions for safe storage, including any incompatibilities		
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.	

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

propane (74-98-6)	
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Propane
OEL TWA	1800 mg/m ³
OEL TWA	1000 ppm
Regulatory reference	Government Notice No. R 904

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

butane, liquefied, under pressure (106-97-8)		
South Africa - Occupational Exposure Limits (Airborne Pollutants)		
Local name	n-Butane	
OEL TWA	1430 mg/m ³	
OEL TWA	600 ppm	
OEL STEL	1780 mg/m ³	
OEL STEL	750 ppm	
Regulatory reference Government Notice No. R 904		

8.2. Appropriate engineering controls

Appropriate engineering controls Environmental exposure controls Ensure good ventilation of the work station.Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection Eye protection Skin and body protection Respiratory protection

- : Protective gloves
- : Safety glasses
- : Wear suitable protective clothing
- : In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Lotion.
Colour	: White.
Odour	: characteristic.
Odour threshold	: No data available
рН	: 6.1 – 7.1
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: Extremely flammable aerosol.
Vapour pressure	: No data available
Vapour pressure at 50°C	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Relative density of saturated gas/air mixture	: No data available
Density	: No data available
Relative gas density	: No data available
Solubility	: No data available

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Partition coefficient n-octanol/water (Log Pow) Partition coefficient n-octanol/water (Log Kow) Viscosity, kinematic Viscosity, dynamic Explosive properties Oxidising properties Explosive limits Lower explosion limit	 No data available No data available No data available 1500 - 2500 mPa·s Pressurised container: May burst if heated. No data available No data available No data available No data available
Upper explosion limit	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects		
Acute toxicity (dermal)	Not classified Not classified Not classified	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))	
butane, liquefied, under pressure (106-97-8)		
LC50 Inhalation - Rat	1442.738 – 1443 mg/l 15 MIN	
LC50 Inhalation - Rat [ppm]	800000 ppm 15 MIN	
Butylmethoxy dibenzoylmethane (70356-09-1)		
LD50 oral rat	> 16000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
(3,3,5-trimethylcyclohexyl) 2-hydroxybenzoate (118-56-9)		
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	

Safety Data Sheet

F

according to SANS 10234:2019 and SANS 11014:2010

(3,3,5-trimethylcyclohexyl) 2-hydroxybenzoat	e (118-56-9)
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Ethylhexyl salicylate (118-60-5)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
octocrilene (6197-30-4)	·
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
Skin corrosion/irritation :	Not classified pH: 6.1 – 7.1
Serious eye damage/irritation :	Not classified pH: 6.1 – 7.1
Respiratory or skin sensitisation	Not classified
Respiratory or skin sensitisation :	Not classified
Germ cell mutagenicity :	
Carcinogenicity :	Not classified
Reproductive toxicity :	Not classified
STOT-single exposure :	Not classified
STOT-repeated exposure :	Not classified
Butylmethoxy dibenzoylmethane (70356-09-1)
LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	450 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	360 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Ethylhexyl salicylate (118-60-5)	·
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents)
octocrilene (6197-30-4)	
LOAEL (oral, rat, 90 days)	340 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	175 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
Aspiration hazard :	Not classified
Fozzi's kids sunscreen lotion spray SPF50	
Vaporizer	Aerosol
propane (74-98-6)	
Animal studies and expert judgment for classification	False
butane, liquefied, under pressure (106-97-8)	
Animal studies and expert judgment for classification	False

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Butylmethoxy dibenzoylmethane (70356-09-1)		
Animal studies and expert judgment for classification	False	
(3,3,5-trimethylcyclohexyl) 2-hydroxybenzoate (118-56-9)		
Animal studies and expert judgment for classification	False	
Ethylhexyl salicylate (118-60-5)		
Animal studies and expert judgment for classification	False	
octocrilene (6197-30-4)		
	False	

SECTION 12: Ecological information 12.1. Toxicity Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. Hazardous to the aquatic environment, short-term : Not classified (acute) Hazardous to the aquatic environment, long-term : Not classified (chronic) propane (74-98-6) LC50 - Fish [1] 50 mg/l (96 h, Pisces, Fresh water, QSAR, Estimated value) Partition coefficient n-octanol/water (Log Pow) 1.1 - 2.8 (Experimental value, 20 °C) butane, liquefied, under pressure (106-97-8) LC50 - Fish [1] 1000 mg/l (96 h, Pimephales promelas, QSAR) Partition coefficient n-octanol/water (Log Pow) 2.8 (Experimental value, 20 °C) Butylmethoxy dibenzoylmethane (70356-09-1) LC50 - Fish [1] > 0.03 mg/l Test organisms (species): Cyprinus carpio EC50 - Crustacea [1] > 0.03 mg/l Test organisms (species): Daphnia magna (3,3,5-trimethylcyclohexyl) 2-hydroxybenzoate (118-56-9) LC50 - Fish [1] > 82 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) EC50 - Crustacea [1] > 100 mg/l Test organisms (species): Daphnia magna Ethylhexyl salicylate (118-60-5) LC50 - Fish [1] > 82 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) EC50 - Crustacea [1] 10 mg/l Test organisms (species): Daphnia magna octocrilene (6197-30-4) EC50 - Crustacea [1] > 0.023 mg/l Test organisms (species): Daphnia magna EC50 72h - Algae [1] > 220 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

Fozzi's kids sunscreen lotion spray SPF50	
Persistence and degradability	No additional information available
propane (74-98-6)	
Persistence and degradability	Readily biodegradable in water.

12.2. Persistence and degradability

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

butane, liquefied, under pressure (106-97-8)		
Persistence and degradability	Readily biodegradable in water.	
12.3. Bioaccumulative potential		
Fozzi's kids sunscreen lotion spray SPF50		
Bioaccumulative potential	No additional information available	
propane (74-98-6)		
Partition coefficient n-octanol/water (Log Pow)	1.1 – 2.8 (Experimental value, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
butane, liquefied, under pressure (106-97-8)		
Partition coefficient n-octanol/water (Log Pow)	2.8 (Experimental value, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
12.4. Mobility in soil		
Fozzi's kids sunscreen lotion spray SPF50		
Mobility in soil	No additional information available	
propane (74-98-6)		
Surface tension	No data available in the literature	
Partition coefficient n-octanol/water (Log Pow)	1.1 – 2.8 (Experimental value, 20 °C)	
Ecology - soil	Not applicable (gas).	
butane, liquefied, under pressure (106-97-8)		
Surface tension	No data available in the literature	
Partition coefficient n-octanol/water (Log Pow)	2.8 (Experimental value, 20 °C)	
Ecology - soil	Not applicable (gas).	
12.5. Other adverse effects		
Ozone : Other adverse effects :	Not classified No additional information available	

SECTION 13: Disposal consid	erations
13.1. Disposal methods	
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with SANS / IMDG / IATA		
SANS	IMDG	ΙΑΤΑ
14.1. UN number		
1950	1950	1950
14.2. Proper Shipping Name		
AEROSOLS	AEROSOLS	Aerosols, flammable

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

SANS	IMDG	ΙΑΤΑ
14.3. Transport hazard class(es)		
2.1	2.1	2.1
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		
14.6. Special precautions for user		
SANS Special provisions (SANS) Limited quantities (SANS) Limited quantities (SANS) Packagings, large packagings and IBCs Packing instructions (SANS) Packagings, large packagings and IBCs Special packing instructions (SANS) IMDG Special provisions (IMDG) Packing instructions (IMDG) Special packing provisions (IMDG) EmS-No. (Fire) EmS-No. (Spillage) Stowage category (IMDG) Stowage and handling (IMDG) Segregation (IMDG)	 63, 190 See SP277 See SP277 P003 PP17, PP87 63, 190, 277, 327, 344, 381, 959 P207, LP200 PP87, L2 F-D - FIRE SCHEDULE Delta - FLAMMABI S-U - SPILLAGE SCHEDULE Uniform - GA None SW1, SW22 SG69 	LE GASES \SES (FLAMMABLE, TOXIC OR CORROSIVE)
IATA PCA Excepted quantities (IATA) PCA Limited quantities (IATA) PCA limited quantity max net quantity (IATA) PCA packing instructions (IATA) PCA max net quantity (IATA) CAO packing instructions (IATA) CAO max net quantity (IATA) Special provisions (IATA) ERG code (IATA)	 E0 Y203 30kgG 203 75kg 203 150kg A145, A167, A802 10L 	

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

SECTION 16: Other information

Issue date Revision date : 28/02/2024 : 28/02/2026

Full text of H-statements	
H220	Extremely flammable gas
H226	Flammable liquid and vapour
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H303	May be harmful if swallowed
H304	May be fatal if swallowed and enters airways
H313	May be harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), South Africa

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.